

TAKE A SMART APPROACH
TO ENTERPRISE WITH

DELTAVIEW SMART INTERACTIVE PANEL













www.**deltaview**.in



SMARTER CONFERENCE SOLUTIONS

Revolutionize corporate efficiency with DeltaView interactive panel for smart corporate solutions. Seamlessly integrate collaborative tools, real-time data analytics, and intuitive interfaces to enhance decision-making. Experience a dynamic platform that empowers teams to engage, share insights, and drive innovation in a connected and intelligent workspace.

Product Specification





Anti-glare coating to absorb up to 80% of light













4K UHD





Powerful channel 2.1 sound 40w with



NFC Reader



Canvas giving sharp,natural writing experience



Anti-glare coating to absorb up to 80% of light



Easy Wireless connectivity with laptops and mobile devices



Open platform, compatible with all e-learning contents



Toughened glass protection 8 MOHS



In-built Wi-Fi 6.0, Ethernet & Bluetooth 5.1



Energy saving design, Max 300W, consumes <0.5W on standby




Wide viewing angle up-to 178 degree

Product Feature's

MULTI FINGURE GESTURE CONTROL

Draw, select, drag, rotate, and erase by using the 40 multi-point touch gesture control like palm erase, double click to change pen colour, long press, multi-finger swipe etc.





ENDLESS CANVAS / AUTO SCROLL

Write endlessly on the smart board without erasing. New pages are automatically created and old pages can be referred anytime during the session.

TEXT/SHAPE RECOGNITION

Recognizes the text or shape written or drawn on the canvas automatically and converts it into the most accurate and readable format.





SCREEN RECORDING

Teachers can record, save, replay, and share the entire lesson conducted on the smart digital screen with the audio and video files.

INTELLIGENT SEARCH

The panel automatically gives the access to online sources (like Google, Wikipedia, Youtube, PubMed) for the topic written and highlighted on the screen. And also share necessary information about topic direct on the canvas.





IMAGE INSERTION / PDF

Image insertaion it helps to insert a image through QR code from mobile to whiteboard.



Product Specifications

MODEL NO.	DV65A1	DV75A1	DV86A1
LED PARAMETERS	65"	75″	86"
DISPLAY			
BACK LIGHT	D-LED	D-LED	D-LED
ACTIVE DISPLAY AREA	1895.04 (H) X 1065.96 (W)	1649.74 (H) X 927.94 (W)	1895.04 (H) X 1065.96 (W)
RESOLUTION	3840 x 2160 (PIXEL, RGB)	3840 x 2160 (PIXEL, RGB)	3840 x 2160 (PIXEL, RGB)
CONTRAST RATIO	1200:1	1200:1	1200:1
BRIGHTNESS	450 CD/M2	450 CD/M2	450 CD/M2
DISPLAY COLORS	1.07B (10 BIT)	1.07B (10 BIT)	1.07B (10 BIT)
ASPECT RATIO	16:9	16:9	16:9
RESPONSE TIME	3MS	3MS	3MS
VIEWING ANGLE	178°(H) / 178°(W)	178° (H) / 178° (W)	178 (H) / 178 (W)
LED LIFE TIME	50,000 HRS (MIN)	50,000 HRS (MIN)	50,000 HRS (MIN)
BONDING TECHNOLOGY	ZERO BONDING	ZERO BONDING	ZERO BONDING
SCREEN PROTECTOR	3MM TEMPERED AG	3MM TEMPERED AG	3MM TEMPERED AG
SCREEN PROTECTOR	GLASS/8MOHs	GLASS / 8MOHs	GLASS / 8MOHs
SPEAKER			
SOUND OUTPUT-SPEAKER		40W	
CAMERA & MIC			
PIXEL	48 - Mega Pixel		
POWER PARAMETERS			
POWER (NO PC)	≤250 W	≤350 W	≤450 W
WORKING VOLTAGE	100V~240V AC	100V~240V AC	100V~240V AC
STANDBY POWER	< 0.5W	< 0.5W	< 0.5W
	5.5.7	0.011	\ 0.5W
ANDROID OS			
ANDROID SYSTEM	ANDROID 13		
MOTHERBOARD	A311D2		
RAM & ROM	DDR4 8GB & EMMC 128GB		
CPU / GPU	OCTACORE, CORTEX A73 + A53, G52MP8		
WIFI	WIFI 5, 802. 11AC/B/G/N/A/AX (2.4GHZ + 5GHZ) : WITH HOTSPOT 5GHZ		
BLUETOOTH	BLUETOOTH 5.1		
UI RESOLUTION	4K UHD		
ETHERNET NETWORK		10M / 100M / 1000M (DEFAULT)	
INPUT & OUTPUT BACK INTERFACE INPUT & OUTPUT	현대 기계에 가장 가장 가장 하는 것이 되었다.	H USB*1, TYPE C*1, HDMI IN*2, USB 2. 1, VGA*1, Rj45 IN*1, Rj45 OUT*1, HDMI	(ATAN) [1] (ATAN (ATAN ATAN ATAN ATAN
FRONT CONNECTION	USB 3.0*2, HDMI IN*1 : TOUCH USB*1 : TYPE C*1		
TOUCH PARAMETERS			
TOUCH TECHNOLOGY		INFRARED TECHNOLOGY (IR)	
TOUCH POINTS	WINDOWS SYSTEM: 40 TOUCH: ANDROID SYSTEM: 40 TOUCH		
NDUCTIVE OBJECTS	FINGURE OR PEN		
ACURACY	Φ1 MM		
OPERATING SYSTEM	SUPPORT WINDOW, MAC, ANDROID, LINUX, CHROME		
ENVIRONMENT			
STORAGE & WORKING TEMPERATURE	WORKING TEMPRA	ATURE: 0C~45 C, STORAGE TEMPE	RATURE: 20 C~60 C
STORAGE & WORKING HUMIDITY	10% ~ 90%		
PACKING PARAMETERS		=11766 N 2528 =	
PHYSIC SIZE	1490.6*904.8*88.95MM	1712.9*1030.9*89.15MM	1958.9*1169.75*89.15 MI
PLYWOOD CARTON SIZE	1576*980*200MM	1785*1125*200MM	2040*1260*200 MM
NET WEIGHT	42+1 KG	54+1 KG	69+1 KG
		04 / NO	Parameter No. 10 and 10
GROSS WEIGHT	56.5+1 KG	69+1 KG	83.8+1 KG

Our Prestigious Client



















Stay Connected, Stay Inspired

Toll Free No: 1800-571-7167

Branch Office:

Delhi | Lucknow | Jaipur

Sales Enquiries: sales@deltaview.in

Training & Support: support@deltaview.in

www.deltaview.in