

TAKE A SMART APPROACH
TO ENTERPRISE WITH

DELTAVIEW SMART INTERACTIVE PANEL













www.**deltaview**.in



SMARTER CONFERENCE SOLUTIONS

Revolutionize corporate efficiency with DeltaView interactive panel for smart corporate solutions. Seamlessly integrate collaborative tools, real-time data analytics, and intuitive interfaces to enhance decision-making. Experience a dynamic platform that empowers teams to engage, share insights, and drive innovation in a connected and intelligent workspace.

Product Specification





Anti-glare coating to absorb up to 80% of light













4K UHD





Powerful channel 2.1 sound 40w with



NFC Reader



Canvas giving sharp,natural writing experience



Anti-glare coating to absorb up to 80% of light



Easy Wireless connectivity with laptops and mobile devices



Open platform, compatible with all e-learning contents



Toughened glass protection 8 MOHS



In-built Wi-Fi 5, Ethernet & Bluetooth 5.1



Energy saving design, Max 300W, consumes <0.5W on standby




Wide viewing angle up-to 178 degree

Product Feature's

MULTI FINGURE GESTURE CONTROL

Draw, select, drag, rotate, and erase by using the 40 multi-point touch gesture control like palm erase, double click to change pen colour, long press, multi-finger swipe etc.





ENDLESS CANVAS / AUTO SCROLL

Write endlessly on the smart board without erasing. New pages are automatically created and old pages can be referred anytime during the session.

TEXT/SHAPE RECOGNITION

Recognizes the text or shape written or drawn on the canvas automatically and converts it into the most accurate and readable format.





SCREEN RECORDING

Teachers can record, save, replay, and share the entire lesson conducted on the smart digital screen with the audio and video files.

INTELLIGENT SEARCH

The panel automatically gives the access to online sources (like Google, Wikipedia, Youtube, PubMed) for the topic written and highlighted on the screen. And also share necessary information about topic direct on the canvas.





IMAGE INSERTION / PDF

Image insertaion it helps to insert a image through QR code from mobile to whiteboard.



BLAZE **Specifications**

MODEL NO.	DV75B13	DV86B13
DISPLAY	75"	86"
BACK LIGHT	0.150	2002
ACTIVE DISPLAY AREA	D-LED	D-LED
PANEL TYPE	1649.74 (H) X 927.94 (W)	1895.04 (H) X 1065.96 (W)
RESOLUTION	3840 x 2160 (4K, RGB)	3840 x 2160 (4K, RGB)
CONTRAST RATIO	1200:1	1200:1
BRIGHTNESS	450 CD/M2	450 CD/M2
DISPLAY COLORS	1.07B (10 BIT)	1.07B (10 BIT)
ASPECT RATIO	16:9	16:9
RESPONSE TIME	2-5 MS	2-5 MS
VIEWING ANGLE	178° (H) / 178° (W)	178° (H) / 178° (W)
LED LIFE TIME	60,000 HRS	60,000 HRS
BONDING TECHNOLOGYY	ZERO BONDING	ZERO BONDING
SCREEN PROTECTOR	3MM TEMPERED	3MM TEMPERED
	AG GLASS/8 MOHS	AG GLASS/8 MOHS
SPEAKER		
SOUND OUTPUT-SPEAKER	20x2W+15W S	UBWOOFERS
CAMERA & MIC		
PIXEL	48 - Mega Pixel	
MICROPHONE	8 ARRAY MIC	
POWER PARAMETERS		
POWER (NO PC)	≤ 350 W	≤ 450 W
WORKING VOLTAGE	100V~240V AC	100V~240V AC
STANDBY POWER	<0.5W	< 0.5W
ANDROID OS	70.044	~ U.5WV
ANDROID SYSTEM		2.42
0.004164-4.000.00001953000.0000	ANDROID 13	
MOTHERBOARD RAM & ROM	A311D2 DDR4 8GB & EMMC 128GB	
CPU / GPU	OCTACORE, CORTEX A73 + A53 ,G52MP8	
WIFI	WIFI 5, 802.11AC/B/G/N/A/AX (2.4GHZ + 5GHZ) : WITH HOTSPOT 5GHZ	
BLUETOOTH	BLUETOOTH 5.1	
ETHERNET NETWORK	10M / 100M / 1000M (DEFAULT)	
INPUT & OUTPUT		1000 Table 1716
	LICE 2 DES TOUCH LICEM TYPE OF	1 HDMI IN*2 USB 2.0*1 AUDIO IN *1
BACK INTERFACE INPUT & OUTPUT	USB 3.0*2, TOUCH USB*1, TYPE C*1, HDMI IN*2, USB 2.0*1, AUDIO IN *1, DP IN*1, VGA*1, RJ45 IN*1, RJ45 OUT*1, HDMI OUT*1	
FRONT CONNECTION	USB 3.0*2, HDMI IN*1 : TOUCH USB*1 : TYPE C*1	
TOUCH PARAMETERS		
TOUCH TECHNOLOGY	INFRARED TECHNOLOGY (IR)	
TOUCH POINTS	WINDOWS & ANDROID SYSTEM: 40 TOUCH POINTS	
INDUCTIVE OBJECTS	FINGER OR PEN	
ACURACY	φ 1 MM	
OPERATING SYSTEM	SUPPORT WINDOWS, MAC, ANDROID, LINUX, CHROME	
	events and design to the execution of the second second second to the second s	en en en en entrette a Control e de Promonie de Salabora de Cal
ENVIRONMENT	WORKING TELEFORM	OTODACE TEMPERATURE AND AND
STORAGE & WORKING TEMPERATURE	WORKING TEMPERATURE: 0°C~45°C, STORAGE TEMPERATURE: 20°C~60°C 10% ~ 90%	
STORAGE & WORKING HUMIDITY	10% -	~ 90%
PACKING PARAMETERS		
PHYSICAL SIZE	1712.9*1030.9*89.15MM	1958.9*1169.75*89.15MM
CARTON SIZE	1785*1125*200MM	2040*1260*200MM
NET WEIGHT	54+1 KG	69+1 KG
GROSS WEIGHT	69+1 KG	83.8+1 KG
	manus profitations	



PRESTIGIOUS CLIENTS



















Stay Connected, Stay Inspired

Contact us
Head Office
Gurugram
Toll Free No
1800-571-7167

Sales Enquiries sales@deltaview.in

Training & Support enquiry@deltaview.in

www.deltaview.in